

DHI-ISC-ETRS-0001

EAS RF Sample Package



- Includes various types of EAS AM samples.
- Suitable for the installation of all kinds of goods to meet the needs of product protection.

Introduction

EAS RF Sample Package contains different kinds of RF tags and related accessories for functional and performance testing. The tags can be fixed on the goods in various forms to achieve the purpose of protection with EAS anti-theft antenna.

Features

EAS Tags Introduction

EAS tag is a kind of anti-theft device containing a specific frequency sensing element. It is installed on the product to be protected and used with anti-theft antenna.

Application Scenarios

Suitable for the display and protection of clothing, daily necessities, tools, 3C electronics and other products.

Target User

Customers interested in purchasing the EAS RF tags.

Technical Specification

Performance Parameters

Technology	Radio-Frequency (RF)
Detection Frequency	8.2 ± 0.25MHZ
Certifications	Conform with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulations as defined in EC No 1907/2006 and subsequent amendments.

Sample Information

Name	Model	Quantity
RF mini Square Tag T001C	DHI-ISC-ETRS-T001C	5
RF Square Tag T004W	DHI-ISC-ETRS-T004W	5

RF Round Tag T013C	DHI-ISC-ETRS-T013C	5
RF Golf Tag T845	DHI-ISC-ETRS-T845	5
RF Mini Pencil Tag T010C	DHI-ISC-ETRS-T010C	5
RF Lanyard Pencil Tag T012C	DHI-ISC-ETRS-T012C	5
RF Bottle Tag B038C	DHI-ISC-ETRS-B038C	5
RF Metal Belt Bottle Tag B008A	DHI-ISC-ETRS-B008A	5
RF Triangle Bottle Tag B005	DHI-ISC-ETRS-B005	5
RF Crab Bottle Tag B040	DHI-ISC-ETRS-B040	5
Cone Steel Pin Smooth P106A	DHI-ISC-ET-P106A	5
Cone Steel Pin Groove P106B	DHI-ISC-ET-P106B	5
Flat Steel Pin Smooth P101A	DHI-ISC-ET-P101A	5
Flat Steel Pin Groove P101B	DHI-ISC-ET-P101B	5
Flat Swivel Smooth Pin P702A	DHI-ISC-ET-P702A	5
Elliptic Smooth Pin P742R	DHI-ISC-ET-P742R	5
Elliptic Smooth Pin P726Y	DHI-ISC-ET-P726Y	5
Lanyard L002B	DHI-ISC-ET5-L002B	5
Lanyard L001W	DHI-ISC-ET5-L001W	5
Stop Lock Tag T705A	DHI-ISC-ET5-T705A	5
Stop Lock Tag 706A	DHI-ISC-ET5-706A	5

Dual-Frequency Mini Alarming Retractable Tag T504-2A-S	DHI-ISC-ETD2A-T504A-S	2
Dual-Frequency Spider T511A-2A-S	DHI-ISC-ETD2A-T511A-S	2
RF Mini Cable 2 Alarming Tag	DHI-ISC-ETR2A-T307-S	2
RF Cable 2 Alarming Tag	DHI-ISC-ETR2A-T301-S	2

General Parameters

Inner Box Dimensions	415 mm × 300 mm × 60 mm (16.34" × 11.81" × 2.36")
Net Weight / Box	0.8 kg (1.76 lb)
Carton Packaging	4 Boxes/Carton
Carton Dimension	430 mm × 320 mm × 260 mm (16.93" × 12.60" × 10.24")
Gross Weight / Carton	4 kg (8.82 lb)
Sales	1 Carton

Environmental Constraints

Operating Temperature	0 °C to 50 °C (32 °F to +122 °F)
Operating Humidity	20 % - 60 % (RH)

Ordering Information

Type	Model	Description
Sample Package	DHI-ISC-ETRS-0001	EAS RF Sample Package